

Whicam[®] Story3 CS

Enjoy Wireless & Auto Focus!

Wireless Autofocus Intraoral Camera with Mouse



-IC-WHT60
-IC-WHC50
-IC-MOZ40
-IC-DZ21
-IC-WHW61
-IC-HCP31
-IC-HCN30

-CL-DL10
-CL-DC20
-CL-AT24

-LS-HM20
-LS-HMT30

-AL-DF10

Enjoy Wireless & Auto Focus!

Wireless Autofocus Intraoral Camera with Mouse

1 Features of Whicam Story3 CS



High speed digital wireless

High speed digital wireless provide more clear live image without interruption.



Auto focus

Real Autofocus function shows clear images.



HD image

High definition show more detail images.



Gyro mouse built-in

Useable as a mouse.



Adjustable head angle

User can use the camera with prefer angle.



280° twist head

Easy to get approach anywhere in oral cavity.



Big capacity battery

Long time use with big capacity battery.



Software compatibility

Support keyboard short-cut data changing program and twain driver.



OLED screen

Bright and clear OLED screen indicates various device status.



Adjustable LED brightness

Can adjust LED brightness to avoid light reflecting.



3 Color Impressions

Can change live image color impression (Original, Warm, Cool)



2 Wireless receiver

- USB power operation

It doesn't need other electric power supply.
The receiver works with USB electric power only.

- Compact design

Compact receiver saves space.

- Unlimited receiver channel

Digital wireless type support unlimited channel.
User can use many receivers with on camera

4 Minimum System Requirement

PC system:	2.0 Ghz CPU, 1GB RAM
OS:	Windows XP service pack 2 (Windows XP 64 bit is not supported)
USB port:	USB 2.0

3 Specification

Model name	IC-WHT60	
Camera (included head)	Operation voltage	3.7V
	Measurement	Approx. 266 x 31 x 37 mm
	Weight	Approx. 140g
	Resolution	1.3 Mega pixel
	Sensor/Lens type	CMOS / Liquid lens
Charger	Measurement	Approx. 169 x 148 x 89 mm
	Weight	Approx. 170 g
	Operation voltage	5V
Disposable cover	Dimensions	Approx. 32 x 100 mm
	Quantity	Approx. 100 pcs by weight x 2ea
	Raw material	Polyethylene
Adapter	Input voltage	AC 100 ~ 240 V
	Output voltage	DC 5V 2A
	UL number	E333054

5 DrsViewer2

Image Viewer included.

